

1. A mobile node moving between IP (Internet Protocol) networks, comprising:

IPv6 (Internet Protocol version 6) processing means for executing services in accordance with said IPv6;

communication processing means for executing transmission/reception control of packets to and from said networks; and

movement registration processing means for adding an IPv4 header (an IP header used for said IPv4), in which an IPv4 address of a mobile agent is set as a foreign address and an IPv4 address of said mobile node usable in a foreign IPv4 network is set as a home address, to a message used for said IPv6 so as to register the movement of said mobile node to said mobile agent connected to an IPv4/v6 network (a network capable of executing communication by utilizing both of said IPv4 and said IPv6) for assisting the movement of said mobile node when said mobile node moves from said IPv4/v6 network to an IPv4 network (a network capable of executing communication by utilizing only said IPv4), and transmitting said message.

2. A mobile node moving between networks,  
comprising:

packet transmission processing means for generating an IPv4 encapsulated IPv6 packet by adding an IPv4 header, in which an IPv4 address of a mobile agent on an IPv4/v6 network is set as a foreign address and an IPv4 address of said mobile node usable for a foreign IPv4 network is set as a home address, to an IPv6 packet (a packet used for said IPv6) transmitted from said mobile node to other nodes when said mobile node moves from said IPv4/v6 network to said IPv4 network, and transmitting said IPv4 encapsulated IPv6 packet.

communication processing means for executing

mobile node management means for managing IPv4 addresses of said mobile nodes usable in a foreign IPv4 network, when receiving a message used for said IPv6 for registering the movement, which said message is transmitted by said mobile node that has moved to said IPv4 network to said mobile agent, and to which an IPv4 header is added; and

IPv4 (Internet Protocol version 4) processing means for executing services in accordance with said

IPv6 processing means for executing services in accordance with said IPv6;

transfer-to-mobile node processing means for generating an IPv4 encapsulated IPv6 packet by adding an IPv4 header, in which an IPv4 address of a mobile node usable in a foreign IPv4 network is set as a foreign IPv4 address and an IPv4 address of said mobile agent is set as a home IPv4 address, to a received IPv6 packet when said transfer-to-mobile node processing means receives said IPv6 packet transmitted by other node to said mobile node that has moved to said IPv4 network, and transmitting said IPv4 encapsulated IPv6 packet.

8. A method of controlling a mobile node by a mobile agent in a network system in which a first IP (Internet Protocol) network capable of executing communication in accordance with first and second kinds of IPs and a second IP network capable of executing communication in accordance with only said first kind of

deleting said first kind of IP header by said second mobile agent and transmitting said IP packet to said mobile node.

9. A method of controlling a mobile node by a mobile agent in a network system in which a first IP (Internet Protocol) network capable of executing communication in accordance with first and second kinds of IPs and a second IP network capable of executing communication in accordance with only said first kind of IP, so that said mobile node capable of executing communication in accordance with said second kind of IP

adding a second kind of an IP header, in which an IP address, in accordance with said second kind of IP, of said mobile node relating to said second IP network is set as a foreign address by a first mobile agent belonging to said first IP network and an IP address, in accordance with said second kind of IP, of said first mobile agent is set as a home address, to an IP packet, in accordance with said second kind of IP, transmitted from said other nodes to said mobile node, adding further a first kind of IP header, in which an IP address, in accordance with said first kind of IP, of said second mobile agent belonging to said second IP network is set as a foreign address and an IP address, in accordance with said first kind of IP, of said first mobile agent is set as a home address, and transmitting said packet to said second mobile agent; and

10. A method of controlling a mobile node by a mobile agent in a network system in which a first IP (Internet Protocol) network capable of executing communication in accordance with first and second kinds of IPs and a second IP network capable of executing

adding a first kind of an IP header, in which an IP address, in accordance with said first kind of IP, of a first mobile agent belonging to said first IP network is set as a foreign address by a second mobile agent belonging to said second IP network and an IP address, in accordance with said first kind of IP, of said second mobile agent is set as a home address, to an IP packet in accordance with said second kind of IP transmitted from said mobile node to said other node, and transmitting said IP packet to said first mobile agent; and

11. A method of controlling a mobile node by a mobile agent in a network system in which a first IP (Internet Protocol) network capable of executing communication in accordance with first and second kinds of IPs and a second IP network capable of executing communication in accordance with only said first kind of





12. A network system for controlling a mobile node and assisting the movement of said mobile node by a mobile agent, in which a first IP (Internet Protocol) network capable of executing communication in accordance with first and second kinds of IPs and a second IP network capable of executing communication in accordance with only said first kind of IP are connected with each other, so that said mobile node capable of executing communication in accordance with said second kind of IP can communicate with other nodes belonging to said first IP network in accordance with said second kind of IP when said mobile node moves from said first IP network to said second IP network, comprising:

a first mobile agent for adding a first kind of an IP header, in which an IP address, in accordance with said first kind of IP, of a second mobile agent belonging to said second IP network is set as a foreign address and an IP address, in accordance with said first kind of IP, of said first mobile agent belonging to said first IP network is set as a home address, to an IP packet in accordance with said second kind of IP transmitted from said other node to said mobile node, and transmitting said IP packet to said second mobile agent; and

said second mobile agent for deleting said first kind of said IP header and transmitting said IP packet to said mobile node.

13. A network system for controlling a mobile node and assisting the movement of said mobile node by a

0066280 09661960















address, in accordance with said first kind of IP, of a second mobile agent belonging to said second IP network is set as a foreign address and an IP address, in accordance with said first kind of IP, of said mobile agent itself is set as a home address, to a message in accordance with said second kind of IP for permitting the movement, and transmitting said message to said second mobile agent.